

UFO V2 SOLAR LIGHT SPECIFICATION



Features

The UFO style of all-in-one solar lighting is designed to be aesthetically pleasing while offering a functional 360° lighting pattern. The premium 3030 LED's provide exceptional light output distributed over a wide area.

The UFO lights unique shape, black coated cast aluminium body adds to the style and provides a corrosion resistant finish suitable for installation in coastal environments. Constant all night lighting, P.I.R (passive infrared sensor) operated or a combination of both are easily programmed by remote control. Designed for use in parks, gardens, courtyards, playgrounds or decks.



Luminaire Height	2.5 - 4m
Lumen Output	2350 lm
LED Output	15W (max)

Stylish and functional solar lighting

360° lighting pattern for illuminating larger areas

Ideal for illuminating courtyards, decks & park areas

Smart Lighting Program

Commercial grade solar lighting

157 lumen per watt output

Corrosion resistant aluminium body with premium finish

Premium LifePO4 battery

Custom powder coated poles manufactured on request

Simple plug and play installation

2 year warranty for faulty workmanship or component failure not influenced by external means

UFO V2 SOLAR LIGHT SPECIFICATION



Applications

Courtyard | Plaza | 360° lighting | Decks

Technical Data

Solar Panel Wattage	32W
LED Output	15W
Lumen Output	2350 lm (max)
Battery Type	LifePO4
Battery Specifications	45AH 3.2V (144Wh)
Correlated Colour Temp (CCT)	5000K
Fixture Size	560 (l) x 560 (w) x 230 (h) mm
Light Source	3030 SMD
Recharge	5 hours
Mounting Height	2.5 - 4 metres
Mounting	76-90mm column - 76mm spigot
Finish	Powder-coated cast aluminium
Warranty Period	2 years
SKU	SOLL020/V2

Mode of Operation

Auto On at dusk. 100% output for 3 hours, 80% 2 hours, 50% until dawn

As we continue to improve the products function and/or design specifications and data provided may change without notice. Errors and omissions accepted.