


# SOLAR FLUSH MOUNT WALKWAY LIGHTS



## Features

The solar flush mounted walkway and cycleway light offers trip hazard free, all-night dusk to dawn lighting that will clearly define a walkway or cycleway. This premium product is at the forefront of solar technology offering a super capacitor as power storage in place of a battery allowing an extended life to greater than 8 years. Various colours and static or flashing modes are options. The light is designed in three parts, the cast aluminium base that is set into the substrate, the removable epoxy filled internal componentry and the non-slip polycarbonate lens. The light is IP68 (submersible) waterproof rated and has a weight rating exceeding 30 tons making it suitable for roadway installations.

- Commercial grade solar walkway/cycleway lights
- Super capacitor technology
- Trip hazard free installation
- Flush mount non-slip surface
- Visible over 800 metres
- 30 ton load rating
- > 8 years life
- Cast aluminium & polycarbonate construction
- IP68 submersible waterproof rating
- Static or flashing
- Various colour options available
- Automatic dusk to dawn lighting
- 3 year warranty for faulty workmanship or component failure not influenced by external means



Luminaire Height	Flush
Lumen Output	50 lm
LED Output	0.2W

# SOLAR FLUSH MOUNT WALKWAY SPECIFICATION



Various colour options available, in static or flashing modes

## Applications

Cycleways | Walkways | Decks | Wharfs | Roadways

## Technical Data

Solar Panel Wattage	<b>0.44W</b>
LED Output	<b>0.02W</b>
Lumen Output	<b>50 lm</b>
Power Storage	<b>Super capacitor</b>
Capacitor Specifications	<b>120F 2.3V</b>
Autonomy	<b>&gt;72 hours</b>
Correlated Colour Temp (CCT)	<b>6000K</b>
Fixture Size	<b>136mm Dia x 52mm</b>
Light Source	<b>Epistar F10</b>
Recharge	<b>3 hours</b>
Mounting Height	<b>Flush with substrate</b>
Mounting	<b>In-ground</b>
Finish	<b>Anti-slip polycarbonate</b>
Warranty Period	<b>2 years</b>
SKU	<b>SOFMSC01</b>

## Mode of Operation

Automatic dusk to dawn operation. Static or flashing. Various colour options available.

As we continue to improve the products function and/or design specifications and data provided may change without notice. Errors and omissions accepted.