
SOLAR RADAR SPEED SIGN





Radar speed signs provide positive visual enforcement of the designated speed limit. These signs have been proven to be effective, particularly with today's highly visual, often distracted drivers. Usually installed in areas where speeding vehicles are in close proximity to pedestrians.

The SOLTECH Solar Radar speed sign utilizes ultra-bright, high quality and long-life LED technology to provide an animated enforcement of the designated speed limit. The minimal current draw of the system is simply and effectively powered using solar energy. A Bluetooth APP (android) allows control over the full dot matrix display area to change the posted speed limit between 00 – 99 Km/h and system analysis. Once the speed is set the radar detects oncoming vehicles and displays the vehicle speed.



Luminaire Height 2.1m - 2.5m

Lumen (+/-) 560Lm

LED Output Variable Signs manufactured to Australian Standards using 3M reflective material

Increase the visibility of the message and improve safety

Reduces the speed of traffic by creating awareness of speed limit

>48 hours autonomy

IP65 Waterproof design

Day and/or night operation

Quality LiFePO4 battery

Simple to install - secures to a 76mm sign post

Efficient and effective visual enforcement

High visibility LED display

Portable or Fixed versions available

2 year warranty for faulty workmanship or component failure not influenced by external means.







SOLAR RADAR SPEED SIGN SPECIFICATION



Applications

Shared zones | Construction zones | College campus

Technical Data

320 x 320m	LED Screen
900 x 600 x 100m	Sign
Red/Gree	Display Colour
Red:620/Green:5	LED Wavelength
≥6000cd/ı Outdoor Highlight	Luminance Density
6	Viewing Angle
1 - 200 Mi	Viewing Distance
1 - 99 km	Speed Range
Aluminum/3M reflecti	Fixed Sign Material
K-Band, 24.1250G	Radar Frequency
1 - 150 Mi	Radar Range
<±1Km	Radar Accuracy
24 Ah 12 (288Wh) LiFeP0	Battery Specifications
Max 11W Average ≤2	Power Consumption
18v 60	Solar Panel
>48 Hours (setting depender	Autonomy
<6 hou	Recharge
2 - 2.5 Mi	Mounting Height
Automatic Dimmi	Display Brightness
IPo	Waterproof Rating
2 yea	Warranty Period
SRSS003/0	SKU

As we continue to improve the products function and/or design specifications and data provided may change without notice. Errors and omissions accepted.





